




NR9803GALK-UTA



3 needle cylinder bed, top and bottom coverstitch machine for hemming with left side fabric trimmer, suction device, pneumatic thread trimmer and presser foot lift



※Application : T-shirt bottom hemming machine


Features



Adjustable needle bar stroke (31 or 33 mm) for different thickness of garments

DLC coated needle bar for oil leakage prevention, lasts in high speed operation

High-end oil seals on bushings for oil leakage prevention in high speed operation



Two types of presser foot for sewing different garments are included in the purchase



Pneumatic thread trimmer is equipped



Pneumatic presser foot lifter is equipped

Headquarters & Factory MORIMOTO MFG. CO., LTD. Osaka, Japan hqeigyo@kansai-special.com




Central European Branch
KANSAI SPECIAL EUROPE GmbH
Düsseldorf, Germany
sales@kansai-special.de









The fabric knife made of super-hard steel lasts longer and secures clean cut of the fabric. The machine comes with the complementary knife for thick material.






The air blower to fold the fabric to be cut, avoiding curl up, as well to help the excess fabric to flow into the pipe.

NR9803GALK-CD-TL2-UTA (Triple Lock System)

Subclass model with **stitch lock system with condensed stitch** to prevent fraying stitches. This machine includes all standard features of NR9803GALK-UTA.




This special thread tension set prevent the stitch fraying at the end of the seam



Condensed stitch device

This device can be turned ON / OFF



Model Name	Application	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
	7	∌	1		↓ ↓ → i i+	mm	→ → inch	<u> </u>	<u>‡mm</u>	€ s.p.m
NR9803GALK-UTA / NR9803GALK- CD-TL2-UTA	Knit	light to medium	UYx128GAS 10-14	5	7/32, 1/4	33mm	6-16 stitch/inch	0.3-2.9	6	5500

