

Belt-loop maker with smocking mechanism



## NW2203GC-MM



3 needle, flatbed, bottom cover-stitch, belt-loop making machine with front fabric knife and 2 spreader 6 thread smocking mechanism

(1) The support (front) presser foot is independent against the main presser foot, so it is easy to remove, and it has a stopper to keep the lifted position. Therefore, it is easy to insert the fabric when starting the operation.

(2) Equipped with adjusting dials, both spring pressure of right and left lower knives can be equally adjusted.

(3) Adjusting knob enables the machine to produce belt-loop from 8mm up to 20mm.

\* For the width over 16mm, the special wide needle plate and feed dogs are needed.

## Features



Design of the smocking can be easily changed from backside of the machine by changing the cam, changing thread variation

% more than 20 cams are available .



Fabric weight	Type of Needle	No. of Thread	Gauge	Needle bar stroke	Stitch length	Diff. feed ratio	Presser foot lift	Max speed
$\boldsymbol{\vartheta}$			<b>↓ ↓</b> →   ←	↓ mm	→    <b>←</b>			(
Medium- heavy	UY128GAS # 16	10	1/4	31 MM	2.1-4.2 mm	N/A	6 mm	2000 rpm

<u>Headquarters & Factory</u> MORIMOTO MFG. CO., LTD. Osaka, Japan hqeigyo@kansai-special.com

You Tube kansaispecialjapan

<u>Central European Branch</u> KANSAI SPECIAL EUROPE GmbH Düsseldorf, Germany sales@kansai-special.de

www.kansai-special.com/www.kansai-special.de

Q