




NR9803GALK-UTC




3 needle cylinder bed, top and bottom coverstitch machine with left side fabric knife and suction device and pneumatic thread trimmer and presser foot lifter for hemming



XApplication: T-shirt bottom hemming machine


Features



Adjustable needle bar stroke (31 or 33mm) for different thickness of garments

DLC coated needle bar for oil leakage prevention, last in high speed operation

High-end oil seals on bushings for oil leakage prevention in high speed operation



Two types of presser foots are include in the purchase for sewing different garments




Pneumatic thread trimmer is equipped



Pneumatic presser foot lifter is equipped

Headquarters & Factory MORIMOTO MFG. CO., LTD. Osaka, Japan hqeigyo@kansai-special.com








NR9803GALK-CD-TL2-UTA

Subclass model with **stitch lock system with condensed stitch** to prevent fraying stitches. This machine includes all standard feature of NR9803GALK-UTA.



This special thread tension set prevent the stitch fraying at the end of the seam

Condensed stitch device

X This device can be turned ON / OFF



Seam of NR9803GALK-CD-TL2-UTA

X This device can be turned ON / OFF

Optional Devices

Supporting attachment for operators to do constant and simple operation.



ABH-1MPneumatic type folder for hemming with knee switch



ABH-1APneumatic type folder for hemming with sensor



ABH-2Automatic sleeve hemming device

Model Name	Application	Material	Needle	No. of threads	Needle gauge	Needle bar stroke	Stitch length	Diff.Feed ratio	Presser foot lift	Maximum Speed
	*	$\boldsymbol{\vartheta}$	1		# #	mm	→ → inch	### ###	<u>+</u>	Sp.m
NR9803GALK-UTA / NR9803GALK- CD-TL2-UTA	Knit	light to medium	UYx128GAS 10-14	5	7/32, 1/4	33mm	6-16 stitch/inch	0.3-2.9	6	5500